



SINGLE USE
SUPER IMAGE QUALITY
VARIETY OF MODELS

SPECIFICATIONS

	PL-1000	PL-2000 (Portable)
Power		Voltage 100-240 VAC Frequency 50/60 Hz Rated input 45 VA
Illumination		Lamp 2W LED Color temperature Lamp life 30,000 hrs 3,000K-7,000K
Function		White balance, Luminance control(+/-), Enhance(0,1,2), Zoom(x1,x2,x3), Freeze, Snap, Record, USB storage
Output		DVI*1, S-Video*1, CVBS*1
Storage		USB (FAT 32)
Dimensions	350mm(W) * 130mm(H) * 425mm(D)	390mm(W) * 270mm(H) * 200mm(D)
Weight	8 kg	7.2 kg
Screen	/	12.1 inch



**Imaging Processor
PL-2000**

Compatible to all our scopes

**Imaging Processor
PL-1000**



Distributed by



Shanghai SeeGen Photoelectric Technology Co.,Ltd.

Add.: 3 Floor, Building No.1 4299 Jindu Road,
Minhang Dist., Shanghai China

www.seegenmed.com

info@seegen.com.cn

+86 021 5429 5355

Briview

Disposable Choledochoscope


Shanghai SeeGen Photoelectric Technology Co., Ltd.

**DISPOSABLE
CHOLEDOCHOSCOPE**

Insertion Dia.

CHV-100-E	4.7mm
CHV-100T-E	5.3mm
CHV-US100-H	3.0mm

Taper-shape distal tip



Working Channel

CHV-100-E	2.2mm
CHV-100T-E	2.6mm
CHV-US100-H	1.2mm




160K
High resolution image

Suction Button



**DISPOSABLE
CHOLEDOCHOSCOPE**

Mode	CHV-100-E	CHV-100T-E	CHV-US100-H
Field of view	110°	110°	110°
Depth of view	5-50mm	5-50mm	5-50mm
Deflection up/down	160°/130°	160°/130°	120°/120°
Insertion dia.	4.8mm	5.3mm	3.0mm
Distal end dia.	4.8mm	5.3mm	3.0mm
Working length	380mm	380mm	600mm
Working channel	2.2mm	2.6mm	1.2mm



Irrigation
(control the flow)

Instrument